



386 Internationale Drive Suite H, Bolingbrook, Illinois 60440  
 Tel: (630) 633-4500 Toll Free: (800) 379-1191 Fax: (630) 296-8100

## Temperature Control SmartWire™

UL Listed and Rated Type CMP or FPLP  
 Multi-Conductor Shielded Plenum Cable

P/N 001320 - 16 AWG 2 Conductor Shielded Plenum

Cable Specifications	
Description:	16 AWG 2 Conductor Bare Copper, Shielded Plenum, UL Subject 444, UL C(UL) CMP or FPLP UL
Conductor Description:	16 (19/29 Bare Copper)
Insulation:	Low-Smoke PVC .008"
Color Code:	Black/White
Shield:	Aluminum Mylar
Drain Wire:	22 AWG 7 Strand Tinned Copper
Jacket:	Low-Smoke PVC .018"
Marking:	TEMPERATURE CONTROL SYSTEM AN BIN DIG IN / OUT A B C D E 0 1 2 3 4 5 6 7 8 9 16 AWG UL C (UL) CMP OR FPLP UL ROHS MADE IN THE USA
Overall Diameter:	.184" Nom.
Conductor DCR:	4.18 Ohms/Mft.
Capacitance:	76 pF/ft Nom.
Impedance:	25 Ohms/Mft.
Temperature and Voltage Rating:	0 C to 75 C / 300 Volt
Cable Weight:	31 Lbs/Mft.



### Flame Rating:

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

### Agencies Approvals:

NEC Article 800, 760; UL C(UL) CMP or FPLP UL, RoHs Compliant, Made in the USA

